

Waterproof Vehicle Tracker



Features

- IP67 dust tight and waterproof rating
- Wide range of power input voltage
- Store and resend up to 50,000 locations
- Pin point cell location
- AGPS support to improve GPS fixing time
- Driver ID (optional)
- Immobilizer (optional)
- Activated by motion/ignition
- Over the air (OTA) firmware/configuration upload
- Built-in antennas, compact size

Specifications

Mechanical and Environmental					
Dimension (L x W x H)	100 x 70 x 32 mm (±2 mm)				
Weight	230 g				
Material	PC-ABS thermoplastic, heat and impact resistant				
IP Rating	IP67				
Operation Temperature	-20°C ~ +60°C				
Storage Temperature	-40°C ~ +85°C				
Electrical					
Battery	Battery Cell	1000 mAh prismatic Li-Ion			
	Operation Temperature	-20°C ~ +60°C			
	Storage Condition	-20°C ~ +35°C, low humidity and no corrosive gas			
	Capacity	1,000 mAh			
Power Supply Input	6 ~ 36 V _{dc} (Current 2A, Ripple < 300mV _{p-p})				
Power Consumption		6V _{dc}	12V _{dc}	24V _{dc}	36V _{dc}
	Transmit	200 mA	120 mA	50 mA	35 mA
	Stand-by	85 mA	45 mA	25 mA	20 mA
	Idle	25 mA	10 mA	8 mA	7 mA



RX-8W

Waterproof Vehicle Tracker

IO Interface and Other		
Input	6 ~ 36 Vdc up to 2A	
	Active high input	
	Active low input	
1-Wire®	iButton	
Output	Immobilizer	
	Buzzer	
SIM Slot	Full size SIM	
USB	Prolific USB-to-Serial Comm Port	
3-Axes Accelerometer	±16G (default)	
Memory Backup	8 MB flash memory	
Antenna	Built-in GPS and GSM antennas	
LED	Amber	GSM
	Red	Power
	Green	GPS
GPS		
Receiver Type	56-channel, GPS L1 C/A, SBAS: WAAS, EGNOS, MSAS	
Acquisition	Cold starts 29 secs, aided starts 5 secs, reacquisition 1 sec	
Sensitivity	Tracking & Nav. -162 dBm, cold starts -148 dBm, warm starts -148 dBm	
Accuracy	Autonomous 2.5 m, SBAS 2.0 m	
Operation Limits	Altitude 50,000 m, velocity 500 m/s, dynamics ≤ 4 g	
Cellular Communication		
Mobile Station Class	Class B	
GSM / GPRS Bands	GSM 850 MHz, E-GSM 900 MHz, DCS 1800 MHz, PCS 1900 MHz	
Packet Switched Data Rate	GPRS multi-slot class 10, coding scheme CS1 – CS4, up to 85.6 kb/s DL, up to 42.8 kb/s UL	
Key Features	Embedded TCP/IP, UDP/IP, HTTP/FTP protocols	
	Network jamming detection, CellLocate & hybrid positioning	



RX-8W

Waterproof Vehicle Tracker

Accessories

Standard
Warranty seals
Optional
USB to serial cable (for configuration use)
ISO-7637 power surge protection box
Immobilizer relay
iButton probe
iButton tag & key fob
Buzzer
Digital temperature sensor
Microphone (audio surveillance)

NOT E:

1. Datasheets are updated as needed and as such, specifications are subject to change without notice.
2. All specifications are measured at an ambient temperature of 25°C, humidity<75%, and nominal input voltage.